

HTML: The Markup Language

[« intro](#)

[documents »](#)

2. Terminology

The following is a list of terms that are used in other sections of this reference.

browsing context

An environment in which UAs present documents to users. A tab or window in a Web browser typically contains a browsing context, as does an [iframe](#), or [frame](#) elements in a [frameset](#).

case-insensitive match

An exact comparison of two strings, codepoint for codepoint, except that the characters in the range [A–Z](#) and the corresponding characters in the range [a–z](#) are considered to also match.

DOM tree

A representation of a document based on the W3C Document Object Model (DOM), as defined in the [\[DOM4\]](#) specification. UAs build representations of documents by parsing them and constructing DOM trees from them.

fallback content

Content associated with embedded content, to be used when the embedded content cannot itself be used (for example, when the embedded content is of an unsupported format).

flow content

[Flow content](#) consists of [flow elements](#) intermixed with [normal character data](#).

HTML producers

HTML authors (that is, people) and applications (such as editors and content management systems) that produce HTML content.

HTML consumers

HTML user agents; that is, applications (such as Web browsers) which consume HTML content.

must

The word *must* is used in this reference to mark document-conformance requirements that are normatively defined in the [HTML5: A vocabulary and associated APIs for HTML and XHTML](#) full specification. [\[HTML5\]](#).

[jump](#)

Note: This reference does not itself normatively define any requirements.

newline

Any of the following:

- a U+000D CARRIAGE RETURN (CR) character
- a U+000A LINE FEED (LF) character
- a U+000D CARRIAGE RETURN (CR) followed by a U+000A LINE FEED (LF) character

phrasing content

Consists of [phrasing elements](#) intermixed with [normal character data](#).

resolve a URL

To resolve a URL to an absolute URL, as defined in [\[HTML5\]](#).

space

Any of the following:

- U+0020 SPACE
- U+0009 CHARACTER TABULATION (tab)
- U+000A LINE FEED (LF)
- U+000C FORM FEED (FF)
- U+000D CARRIAGE RETURN (CR)

top-level browsing context

As defined in [\[HTML5\]](#).

transparent

If the content model of a particular element *foo* is described as *transparent*, it means:

- when element *foo* is a child of a parent element *bar* whose content model is allowed to contain [flow elements](#), then the contents of element *foo* may also contain [flow elements](#)
- when element *foo* is a child of a parent element *baz* whose content model restricts its child elements to only being [phrasing elements](#), then any child elements of element *foo* are also restricted to only being [phrasing elements](#)

UA

An HTML user agent; that is, an application (such as a Web browser) which consumes HTML content.

[« intro](#)

[documents »](#)

jump